

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 02015164
PUBLICATION DATE : 18-01-90

APPLICATION DATE : 04-07-88
APPLICATION NUMBER : 63166160

APPLICANT : RAIMUZU:KK;

INVENTOR : HIDA SHUJI;

INT.CL. : C23C 14/16 C23C 16/06 C23C 28/02

TITLE : COMPOSITE MATERIAL

ABSTRACT : PURPOSE: To provide superior lightweight characteristic and heat resistance and also to improve oxidation resistance at high temp. by coating the surface on which Pt or Pt-Al phase is formed with a thin-film layer of TiAl-type intermetallic compound.

CONSTITUTION: The surface of a base material composed of Ti or Ti alloy on which Pt or Pt-Al phase is formed by means of the implantation of Pt ions or Pt and Al ions is coated with TiAl-type intermetallic compound. By the above procedure, on exposure to high-temp. oxidizing atmosphere, Al diffused from the resulting thin-film layer is allowed to react with the Pt phase or Pt-Al phase on the base-material surface and fixed in the form of Pt-Al compound, by which the diffusion of Al in the thin-film layer into the base material can be prevented. As a result, sufficient amounts of Al can be incorporated to the thin-film layer and Al_2O_3 contributing as an oxidation protective film can be formed on the surface of the thin-film layer of TiAl-type intermetallic compound in a high-temp. oxidizing atmosphere, by which high- temp. oxidation resistance due to the thin-film layer of intermetallic compound $TiAl_3$ as well as the superior lightweight characteristic and heat resistance of Ti alloy, etc., can be obtained.

COPYRIGHT: (C)1990,JPO&Japio



(19)

(11) Publication number: **02**

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **63166160**(51) Int'l. Cl.: **C23C 14/16 C23C 16/28/02**(22) Application date: **04.07.88**

(30) Priority:

(43) Date of application publication: **18.01.90**

(84) Designated contracting states:

(71) Applicant: **RAIMUZU:KK**(72) Inventor: **HAYASHI TOKIAK
HIDA SHUJI**

(74) Representative:

(54) COMPOSITE MATERIAL

(57) Abstract:

PURPOSE: To provide superior lightweight characteristic and heat resistance and also to improve oxidation resistance at high temp. by coating the surface on which Pt or Pt-Al phase is formed with a thin-film layer of TiAl-type intermetallic compound.

CONSTITUTION: The surface of a base material composed of Ti or Ti alloy on which Pt or Pt-Al phase is formed by means of the implantation of Pt ions or Pt and Al ions is coated with TiAl-type intermetallic compound. By the above procedure, on exposure

to high-temp. oxidizing atmosphere, Al diffused from the resulting thin-film layer is allowed to react with the Pt phase or Pt-Al phase on the base-material surface and fixed in the form of Pt-Al compound, by which the diffusion of Al in the thin-film layer into the base material can be prevented. As a result, sufficient amounts of Al can be incorporated to the thin-film layer and Al₂O₃ contributing as an oxidation protective film can be formed on the surface of the thin-film layer of TiAl-type intermetallic compound in a high-temp. oxidizing atmosphere, by which high- temp. oxidation resistance due to the thin-film layer of intermetallic compound TiAl₃ as well as the superior lightweight characteristic and heat resistance of Ti alloy, etc., can be obtained.

COPYRIGHT: (C)
1990,JPO&Japio